

Liwal Smart Video IP Phone

LA2-V100

The new executive smart Video IP Phone with color touchscreen is a communication power house offering multi-platform video conferencing solution.

With built-in HD video camera and HDMI out port to compliment features.



SPECIFICATIONS

LCD Display	7 Inch TFT (800 x 480) Capacitive Multi-touch Screen
Lines	6 SIP Lines (Supports 6 SIP Servers and Backup SIP proxy servers)
HD Audio	HD Microphone and HD Speaker
Network Interfaces	Dual Gigabit Ethernet Ports with POE and bridged port for PC bypass, QoS, VLAN
Protocols	SIP 2.0 over UDP/TCP/TLS, SRTP, STUN, DHCP, Static, PPPoE, 802.1x, L2TP, PPTP, IPSec, SNTP, HTTP/HTTPS, TR069, Auto-Provisioning, Liwal Web GUI Management Portal
Codec	Narrowband G.711 μ /a, G.723.1, G726-32K, G.729 A/B, iLBC, AMR and Wide-band G.722 In-band and Out-of-Band DTMF Relay RFC2833, SIP INFO
Video Features	Codec H.264, H.263, Image Codec: JPEG, PNG, BMP, GIF, format: MP4/3GP/FLV Call resolution: QCIF, CIF, VGA, 4CIF (1280 x 720P Optional), Bandwidth selection 64kbps~4Mbps, Frame rate selection 10~30fps, Picture-in-Picture (PIP), Video from remote site can be displayed in full screen, supports up to 4 video display mode
Connectivity Interfaces	HDMI Port - Type A, SD Interface - TF Card Support Upto 32G, USB Port- USB 2.0
Headset/Hands-free	Handset, Hands-free (EHS supporting Plantronics headsets), RJ9 Headset Jack
Form Factor	Desktop and Wall Mountable with Desktop Stand
Call Features	Call out/answer/reject/hold/resume/waiting, transfer (Attended/Unattended), Forwarding (Always/Busy/No Answer), Mute/Unmute (mic), Intercom, Caller ID, Speed Dial, Anonymous Call (Hide Caller ID), Parking/Pick-up (depending on server), Redial/Auto-Redial, Do-Not-Disturb, Auto-Answering, 3-way conferencing, Voice Message (on server)
Phone Features	Phonebook (up to 2000 entries), Remote Phonebook (XML/LDAP), Call log (1500 entries), Black/White List Call Filtering, Voice Message Waiting Indication (VMWI), Programmable Soft keys, Network Time Synchronization, Action URL/Active URI
Security	User and Administrator level access control
Power	Universal Power Adapter 100-240VAC 50-60Hz, DC Power Input 5V 1.0A
Temperature/Humidity	Operation Temperature: 0~40°C, Operation Humidity: 10~65%
Package	LA2-V100 Phone, Handset, Cord, Base Stand, Power Adapter, Ethernet Cable, Quick Installation Guide
Compliance	CE, FCC and RoHS
Physical	Box Dimensions: 290 x 260 x 70 mm (L x W x H), Phone Weight: 1.2 Kg; Box Weight: 1.8kg, Phone Color: Black, Environmental friendly box

