



Liwal General Trading LLC
PO.BOX 120734,Dubai, United Arab Emirate
Tel:+ 971508447305
Email: sales@liwal.ae
Internet: : www.liwal.ae

LTOS Outdoor Series

Digital Display, showing voltage, current, power, power factor etc.
Fast response: with less than 10 millisecond response time, ensure uninterruptible power supply for any computer automated equipments and instruments.
Powerful overloading capability: Continuous loading capability at 80% rated power, withstand of 10 times rated current for 10ms, 3 times rated current for 1 minute.
No waveform distortion, with Zero Current Transition technology, properly avoid current breakdown,spikes, surges during the transition.
Sufficient protection, With overload protection, over voltage protection, low voltage protection,short circuit protection, over heat protection and malfunction diagnosis function. Waterproof Rate IP 65

Model	LS30KVAS
Nominal Power	30KVA
Rated Power	24KW
Power Factor	0.6~1.0
Input	
Operating Voltage Range	175-470VAC
Regulation Voltage Range	190-460VAC
Frequency	50Hz/60Hz
Connection Type	Input terminal block
Output	
Output Voltage	380VAC / 400VAC
Operating Voltage	190V-415VAC
High Cut Voltage	415V
Low Cut Voltage	190V
Frequency	50Hz/60Hz
Safety Cycle	6 Seconds / 180 Seconds Selectable
Connection Type	Output terminal block

Regulation	
Number of Taps	Stepless
Transformer Type	Servo Motor Toroidal auto transformer
Regulation Type	Servo motor type
Indicators	
LCD Display	showing input voltage, output voltage, Loading capacity, current, Power factor. Available in setting up output voltage, Frequency...output precision
Protection	
Over Temperature	Auto Shutdown at 120 °C
Short Circuit	Auto Shutdown
Breaker / Fuse	50A
Overload	Auto Shutdown
Over / Under Voltage	Auto Shutdown
Physical	
Weight	260kgs
Dimension	0.77*0.61*1.15m
Product specifications are subject to change without further notice	

Product Details



